

# //// TERRACO®

# Handycoat® 3-in-1

هاندي كوت 3 في 1

• Primer • Stucco • Paint  
دهان بريمر معجون

## Versatility at your fingertips!

- A versatile, multi-functional product for interior use
- Quick and easy to apply
- Low VOC
- Tint if required to light pastel shades
- Quick drying, overcoat in 2 hours

## تعدد الاستخدامات في تناول يديك

- منتج متعدد الاستخدامات للاستعمال الداخلي
- سهل وسريع التركيب
- يحتوي على نسبة ضئيلة من المركبات العضوية المتطايرة
- يمكن تلوينه باللون فاتحه
- سريع الجفاف ، ممكن طلاءه بعد ساعتين



The House of Scandinavian Finishing Materials

# Handycoat®

3-in-1

• Primer • Stucco • Paint

# هاندي كوت®

٣ في ١

• معجون • بريمر • دهان

Now plastering and painting contractors can use the same product for three different purposes - reducing wastage and saving money whilst achieving a high quality finish.

## Product Description


Handycoat 3-in-1 is ready-to-use, environmentally friendly primer, stucco or interior paint depending upon the dilution ratio.

## Uses

Handycoat 3-in-1 is designed for dry interior areas and is suitable for residential, industrial and commercial use either as a primer, stucco or an interior paint depending upon dilution with clean water as follows:

### • Primer

Dilute Handycoat 3-in-1 with 40 - 45% (by weight) of clean, fresh water and you have an excellent compound for priming masonry and gypsum boards.




### • Stucco

Direct from the bucket, Handycoat 3-in-1 is used as a stucco putty to repair and smoothen walls and ceiling prior to priming and painting.



### • Interior Paint

Dilute Handycoat 3-in-1 with 35 - 40% (by weight) of clean, fresh water and it becomes an excellent and economical interior paint for walls and ceilings. It can be tinted to light pastel shades with pigment pastes if required.



الآن طبقه بلاستر ودهان وأساس ، ويمكن الآن للمقاولين استخدام نفس المنتج لمدة ثلاثة أغراض مختلفة - مع تقليل الفاقد وتوفير المال في حين تحقيق الانتهاء من جودة عالية

## وصف المنتج

هاندي كوت ٣ في ١ جاهزة للاستخدام، التمهيدي صديق للبيئة، سائل اساس ومعجون و الطلاء الداخلي تبعا لنسبة التخفيف.

## طريقه الاستخدام

هاندي كوت ٣ في ١ تم تصميمه من أجل المناطق الداخلية الجافة مناسبة للاستخدام السكني والصناعي والتجاري إما التمهيدي، البلاستر أو الطلاء الداخلي تبعا لتخفيف بالماء النظيف على النحو التالي

### • سائل أساس (بريمر)

هاندي كوت ٣ في ١ مع ٤٠ - ٤٥٪ من حجم المياه النظيفة، والطارجة ويكون لديك مركب لبناء طبقه دهان أولى الجبس

### • هاندي كوت

يستخدم الهاندي كوت ٣ في مباشره امن الدلو و يستخدم لتصليح وتعيم الحوائط والأسقف من قبل الاساس والدهان

### • الطلاء الداخلي

هاندي كوت ٣ في ١ مع ٣٥ - ٤٠ ٪ من حجم المياه النظيفة، والطارجة ويصبح الطلاء الداخلي ممتازة واقتصادية للجدران والأسقف ويمكن ملون لظلال فاتح اللون مع المعاجين الصباغ إذا لزم الأمر.

Application	Material Consumption (kg / m <sup>2</sup> )	Dilution Rate (by weight)	Application Tools
Primer	0.12 to 0.15 kg /m <sup>2</sup> or 225 m <sup>2</sup> /25 kg bucket	40 - 45% (10 - 11 Ltr)	Brush/roller
Stucco	0.3 to 0.5 kg/m <sup>2</sup> or 70-80 m <sup>2</sup> /25 kg bucket	0.5% (1-1.2 Ltr)	Trowel/spatula
Interior Paint	0.15-0.2 kg/m <sup>2</sup> or 175 m <sup>2</sup> /25 kg bucket	35 - 40% (9 - 10 Ltr)	Brush/roller/spray

TECHNICAL DATA			
Product	Multi purpose primer – stucco – paint compound	pH value	8.0-8.5
Binders	Acrylic	Drying Time	2-4 hours
Fillers / Pigments	Calcium carbonate / inorganic oxides	Packaging	25kg & 5kg plastic pails
Viscosity	100,000 cps (Stucco)	Storage	12 months in original unopened containers
Specific Gravity	1.70		

For more information please refer to the Terraco Technical Data Sheet or contact your nearest Terraco representative.

www.terraco.com

SWEDEN • UK • IRELAND • RUSSIA • TURKEY • SOUTH AFRICA • JORDAN • EGYPT • UAE • PAKISTAN • THAILAND • VIETNAM • CHINA • KOREA

