

OVERVIEW

Terracryl is a general-purpose, one-pack acrylic joint mastic and crack repair filler, for interior and exterior use. It forms a water-resistant joint and a dust and damp proof seal in situations too demanding for normal mastics. Terracryl is available in white and bronze.

PROPERTIES

Terracryl is a blend of pure acrylic polymers and precisely graded fillers and pigments. The product has the following characteristics:

- Waterproof.
- Weather resistant.
- Permanent flexibility ($\pm 15\%$).
- Quick drying.
- Easy to apply.
- High adhesion to most building surfaces.
- Can be painted after 24 hours.

AREAS OF USE

- Between concrete elements.
- Around doors & windows.
- Behind skirtings and architraves.
- To repair cracks in plaster and concrete.

PREPARATION OF SURFACE

Ensure that all dust, dirt and foreign matter are brushed and scraped away. Also ensure the joint is solid, free from salts, oil, grease and ridges. Clean aluminium surfaces with white spirit. On firm, dust-free surfaces the use of a primer is not necessary. For surfaces that show signs of constant dusting or flaking, or for joints where constant high movement is anticipated, priming using Penetrating Primer is recommended.

APPLICATION & CLEANING OF TOOLS

Cut the nozzle of the Terracryl cartridge at a 45 degree angle. Load the full cartridge into the gun, and starting at a junction or a convenient location, slowly and evenly extrude a continuous bead of Terracryl into the joint, making sure the gun is constantly moving. If necessary, smooth the applied layer with a spatula or a small trowel to ensure good adhesion to the side of the joint. Terracryl is quick-drying and can be painted 24 hours after application.

Clean tools and equipment with water after use.

HEALTH & SAFETY

Avoid prolonged contact with eyes and skin. For detailed information refer to relevant material safety data sheet.

PACKAGING & STORAGE

Terracryl is supplied in 0.5kg cartridges, 5kg and 25 kg containers.

Store containers in a clean dry area protected from direct sunlight and extreme heat and cold. Unopened containers can be stored for 12 months. Use oldest material first.

TERRACO offers a comprehensive range of products and services for most concrete and finishing needs. Please contact the TERRACO Technical Service Department or your local TERRACO agent for further information, samples, demonstrations and instructor services. The information given in this leaflet is based upon laboratory research, as well as extensive field work and application. All products are sold subject to standard conditions of sale which are available on request. This information is based on TERRACO's present state of knowledge and is intended to provide general information on TERRACO's products and their methods of use. The prospective user is recommended to determine the suitability of TERRACO's suggestions and products before adopting them on a commercial scale.

TECHNICAL DATA

Product	Ready-mixed acrylic joint mastic
Binders	Acrylic co-polymer
Fillers	Fine precisely graded fillers.
Dilution	With water if required.
Material Consumption	One cartridge will fill 2 linear metre of a joint size 10 x 15 mm.
Specific Gravity	1.50-1.55
Colour	White and bronze.
Expansion	± 15% of original joint width.
Temperature	-30°C to +90°C
Age Resistance	Excellent
Toxicity	Non-toxic.
Standards	ASTM D 1737, DIN 53217
Packaging	0.5kg cartridges, 5kg and 25 kg containers.
Storage	12 months in original unopened containers.

For technical enquiries please contact your nearest Terraco representative:

CHINA:

Terraco Architectural Coatings China Co., Ltd.
 Tel: +86 (0)20 8759 4742
 Fax: +86 (0)20 8526 8056
 E-mail: sales@terraco.com.cn
 Web: www.terraco.com.cn

Terraco Chemical (Shanghai) Co., Ltd.

Tel: +86 (0)21 621020 48 / 18
 Fax: +86 (0)21 625205 47
 Email: sales@terraco.com.cn
 Web: www.terraco.com.cn

EGYPT:
Terraco Egypt Chemical Industries S.A.E.

Tel: +20 (0)22 29184 53 / 57 / 58
 Fax: +20 (0)22 29184 80
 E-mail: terraco@terraco.com.eg
 Web: www.terraco.com.eg

JORDAN:
Jordan Swedish Polymers Industrial Corp.

Tel: +962 (0)6 553 8751
 Fax: +962 (0)6 553 6560
 E-mail: terraco@nol.com.jo
 Web: www.terraco.jo

IRELAND:
Terraco Technical Centre, Ireland

Tel: +353 (0) 404 66555
 Fax: +353 (0) 404 66654
 E-mail: technical-centre@terraco.com
 Web: www.terraco.com

PAKISTAN:

Terraco Pakistan Pvt. Ltd.
 Tel: +92 (0)42 3529 70 56-8
 Fax: +92 (0)42 3529 70 55
 Email: terraco@terraco.pk
 Web: www.terraco.com

ROMANIA:

Terraco Romania SRL
 Tel: +40 (0)749 203 133
 Fax: +40 (0)318 148 810
 E-mail: ahaque@terraco.com
 Web: www.terraco.com

RUSSIA:

OOO Terraco Sweden Ltd, Russia
 Tel: +7 (0)495 9212 237
 Fax: +7 (0)495 6273 881
 E-mail: adm@terraco.ru
 Web: www.terraco.ru

OOO Terraco Vostok Ltd

Tel: +7 (0)4212 410563
 Fax: +7 (0)4212 410591
 E-mail: terracovostok@terrakovostok.ru
 Web: www.terraco.com

SOUTH KOREA:

Terraco Korea Co., Ltd
 Tel: +82 (0) 2 5611 551
 Fax: +82 (0)2 5671 771
 E-mail: terraco@terraco.co.kr
 Web: www.terraco.co.kr

THAILAND:

Terraco Industry (Thailand) Limited
 Tel: +66 (0)2 946 68 56 / 58
 Fax: +66 (0)2 946 68 59
 E-mail: terraco@terraco.co.th
 Web: www.terraco.com

TURKEY:

Terraco Yapi Malzemeleri Sanayi Ve Ticaret AS
 Tel: +90 (0)222 236 0423
 Fax: +90 (0)222 236 0425
 E-mail: terraco@terraco.com.tr
 Web: www.terraco.com.tr

UAE:

Terraco UAE Ltd
 Tel: +971 (0)4 326 2699
 Fax: +971 (0)4 326 2733
 E-mail: terraco@terraco.ae
 Web: www.terraco.com

UK:

ADDAGRIP
 Tel: +44 (0)1825 761 333
 Fax: +44 (0)1825 768 566
 E-mail: sales@addagrip.co.uk
 Web: www.addagrip.co.uk / www.terraco.com

VIETNAM:

Terraco Vietnam Co., Ltd
 Tel: +84 (0)650 3 820 100
 Fax: +84 (0)650 3 820101
 E-mail: terraco@terraco.com.vn
 Web: www.terraco.com