

1. IDENTIFICATION OF PREPARATION

Product Code and Names:

61655 - Terrabontile Exterior S	61656 - Terrabontile Exterior R	62310 - Terrabontile
62320 - Handytex	62330 - Antique Stucco	62340 - Marblecoat
63175 - Acrylic Filler Jointing Compound	63190 - Handycoat ST	63210 - Acrylic Filler
63251 - Flexipave Filler	63260 - Maxicoat	63410 - Sprayplaster Finishcoat
63430 - Sprayplaster Washable	63460 - Sprayplaster Basecoat	65110 - Terrapaste
65117 - Terrapaste P12	65121 - Terrapaste P22	65122 - Terrapaste P23
65610 - Maxi Tilepaste	67133 - Flexipave Resurfacer	69140 - EnviroTac 200
69160 - EnviroTac 100		

Chemical Name:

Mixture of acrylic emulsions and mineral fillers.

CAS Number:

Blend

Identification of Company:

<p>CHINA: Terraco Architectural Coatings China Co., Ltd. Tel: +86 (0)20 8759 4742 Fax: +86 (0)20 8526 8056 E-mail: sales@terraco.com.cn Web: www.terraco.com.cn</p> <p>Terraco Chemical (Shanghai) Co., Ltd. Tel: +86 (0)21 621020 48 / 18 Fax: +86 (0)21 625205 47 Email: sales@terraco.com.cn Web: www.terraco.com.cn</p> <p>EGYPT: Terraco Egypt Chemical Industries S.A.E. Tel: +20 (0)22 29184 53 / 57 / 58 Fax: +20 (0)22 29184 80 E-mail: terraco@terraco.com.eg Web: www.terraco.com.eg</p> <p>JORDAN: Jordan Swedish Polymers Industrial Corp. Tel: +962 (0)6 553 8751 Fax: +962 (0)6 553 6560 E-mail: terraco@nol.com.jo Web: www.terraco.jo</p> <p>IRELAND: Terraco Technical Centre, Ireland Tel: +353 (0) 404 66555 Fax: +353 (0) 404 66654 E-mail: technical-centre@terraco.com Web: www.terraco.com</p>	<p>PAKISTAN: Terraco Pakistan Pvt. Ltd. Tel: +92 (0)42 3529 70 56-8 Fax: +92 (0)42 3529 70 55 Email: terraco@terraco.pk Web: www.terraco.com</p> <p>ROMANIA: Terraco Romania SRL Tel: +40 (0)749 203 133 Fax: +40 (0)318 148 810 E-mail: ahaque@terraco.com Web: www.terraco.com</p> <p>RUSSIA: OOO Terraco Sweden Ltd, Russia Tel: +7 (0)495 9212 237 Fax: +7 (0)495 6273 881 E-mail: adm@terraco.ru Web: www.terraco.ru</p> <p>OOO Terraco Vostok Ltd Tel: +7 (0)4212 410563 Fax: +7 (0)4212 410591 E-mail: terracovostok@terraco.khn.ru Web: www.terraco.com</p> <p>SOUTH KOREA: Terraco Korea Co., Ltd Tel: +82 (0) 2 5611 551 Fax: +82 (0)2 5671 771 E-mail: terraco@terraco.co.kr Web: www.terraco.co.kr</p>	<p>THAILAND: Terraco Industry (Thailand) Limited Tel: +66 (0)2 946 68 56 / 58 Fax: +66 (0)2 946 68 59 E-mail: terraco@terraco.co.th Web: www.terraco.com</p> <p>TURKEY: Terraco Yapi Malzemeleri Sanayi Ve Ticaret AS Tel: +90 (0)222 236 0423 Fax: +90 (0)222 236 0425 E-mail: terraco@terraco.com.tr Web: www.terraco.com.tr</p> <p>UAE: Terraco UAE Ltd Tel: +971 (0)4 326 2699 Fax: +971 (0)4 326 2733 E-mail: terraco@terraco.ae Web: www.terraco.com</p> <p>UK: ADDAGRIP Tel: +44 (0)1825 761 333 Fax: +44 (0)1825 768 566 E-mail: sales@addagrip.co.uk Web: www.addagrip.co.uk / www.terraco.com</p> <p>VIETNAM: Terraco Vietnam Co., Ltd Tel: +84 (0)650 3 820 100 Fax: +84 (0)650 3 820101 E-mail: terraco@terraco.com.vn Web: www.terraco.com</p>
---	---	--

2. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	Amount	CAS Number
Water:	>15.0%	7732-18-5
Acrylic/Vinyl Polymer:	<15.0%	Proprietary
Calcium Carbonate and/or Dolomite:	>50.0%	1317-65-3 / 163389-88-1

3. HAZARDS IDENTIFICATION

Not classified as dangerous for supply. Avoid inhalation of dust during mixing.	
Potential Health Effects	
Eye	Contact may cause irritation.
Skin	Prolonged contact may dry the skin resulting in irritation and dermatitis.
Inhalation	Avoid inhalation if product atomised during application, may cause respiratory tract irritation.
Ingestion	Ingestion is not considered a potential route of exposure.

4. FIRST AID MEASURES

General	In all cases of doubt or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.
Eye Contact	Flush eye with water for 15 minutes, holding eye lids apart. Get medical attention if irritation develops.
Skin Contact	Remove contaminated clothing. Wash skin with soap and water or a proprietary skin cleaner.
Inhalation	If exposed to excess levels of dust remove to fresh air.
Ingestion	If accidentally swallowed, obtain immediate medical attention. Show this safety data sheet. Do not induce vomiting. If conscious give milk or water to drink.

5. FIRE FIGHTING MEASURES

Flammable Properties	C.O.C. Flash Point:	None
	T.C.C. Flash Point:	None
	Auto ignition temperature:	None
Flammable Limits In Air	L.E.L.	None
	U.E.L.	None
Extinguishing Media	Recommended: Alcohol resistant foam, CO ₂ , Powder, Water spray mist.	
Fire and Explosion Hazards	<p>During a fire, acrylic monomers may be generated at elevated temperatures.</p> <p>If engulfed by ongoing fire do not allow fire fighting run off to enter drains or watercourses.</p> <p>As in any fire wear self-contained breathing apparatus, pressure demand MSHA/NIOSH (approved or equivalent) and full protective gear.</p>	

6. ACCIDENTAL RELEASE MEASURES

Safeguards (Personnel)	Exclude all non-essential personnel. Wear appropriate personal protective equipment.
Initial Containment	<p>Absorb spills with inert material, allow to solidify and scrape up. Do not allow to enter drains or watercourses, clean preferably with a detergent. Do not use solvents.</p> <p>If the product accidentally enters, rivers, lakes, drains or sewers, the Local Authority should be contacted immediately.</p>

7. HANDLING AND STORAGE

General	Smoking, Eating and Drinking should be prohibited in areas of storage or use. Never use pressure to empty the container. Good housekeeping and regular safe removal of waste materials are recommended.
Recommended Storage Temperature	Minimum: 5C (41F) Maximum: 35C (95F)
Shelf Life	12 months in original sealed containers.
Storage Precautions	Avoid extremes of temperature. Keep out of reach of children. Store separately from Oxidising Agents, and strongly acidic or alkaline materials.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Limits	No information presently available.
Engineering Controls	If user operations generate dust, fumes or mist, use local exhaust ventilation and good general extraction.
Personal Protection	
Respiratory Protection	Should not be necessary under normal conditions of use. However suitable respiratory protective equipment should be worn during spray application.
Skin Protection	For brief contact normal work attire should be sufficient. For anticipated prolonged contact, barrier creams should be applied before work is commenced. Suitable gloves should be worn.
Eye Protection	Splashes in eyes may cause irritation; it is recommended that goggles designed to protect against liquid splashes should be worn.

9. PHYSICAL AND CHEMICAL PROPERTIES

Form	High viscosity paste
Odour	Slight acrylic odour
Boiling Point	100 C
Solubility In Water	Dispersible
Specific Gravity	1.6-1.8 (Water =1)
pH	8-9
Volatile Organic Compounds	< 100 gm./ lt.

10. STABILITY AND REACTIVITY

Stability	Stable.
Polymerisation	Product will not undergo polymerisation.
Incompatibility With Other Material	Incompatible with oxidising agents and strongly acidic and alkaline materials.
Decomposition	May produce acrylic monomers and oxides of carbon on decomposition.

11. TOXICOLOGICAL INFORMATION

There is no data available on the products themselves.
 Repeated or prolonged contact may lead to removal of natural fats from the skin, resulting in non-allergic dermatitis and absorption through the skin.
 The products contain small amounts of biocides, not present in quantities sufficient to induce sensitisation by skin contact, but which could elicit an allergic reaction in an already sensitised person.
 Splashes in eyes may cause irritation and reversible local damage.
 Ingestion may result in sore throat, abdominal pain or nausea.

12. ECOLOGICAL INFORMATION

There is no data available on the products themselves. They should not be allowed to enter drains or watercourses.

13. DISPOSAL CONSIDERATIONS

Do not allow to enter drains and watercourses or anywhere that may affect ground or surface waters. Wastes including emptied containers should be disposed of in accordance with the regulations of the Local Authority.

14. TRANSPORT INFORMATION

To transport within the user's premises, always use closed containers that are secure and upright. Ensure that operational personnel know what to do in event of spillage.

D.O.T. SHIPPING NAME:	Not Applicable
D.O.T. HAZARD CLASS:	Non-Hazardous
IATA HAZARD CLASS/PACKAGING GROUP:	Not regulated

15. REGULATORY INFORMATION

The products are determined as not being dangerous for supply according to current Chemicals Hazard Information and Packing Regulations in force.

The information contained in this Material Safety Data Sheet, does not substitute the user's own responsibility to carry out an assessment of work place risks as may be required by Health and Safety Legislation.

16. OTHER INFORMATION

The products should not be used for purposes other than those shown on the manufacturer's product labels and technical data sheets. As the specific conditions of use are outside the supplier's control; the user is responsible for ensuring compliance with the relevant legislation in the territory of use.

The information contained in this Material Safety Data Sheet, is based on the current state of knowledge and current state of Legislation. It provides guidance on Health Safety and Environmental aspects of the products, and should not be taken as a guarantee of technical performance or suitability for particular applications.

Approved by:	J. Carey - Group Technical Director.
Approval date:	04/11/2011
Supersedes:	22/03/2011
Number:	MSDS No. 1008

This information is furnished without warranty, expressed or implied, except that it is accurate to the best of TERRACO's knowledge. The data on this sheet are related only to the specific materials designated herein. TERRACO assumes no legal responsibility for use or reliance upon this data.