

OVERVIEW

Handycoat Exterior is a ready to use filler for use on all common building surfaces, including timber. It gives a high quality, even surface for painting. Handycoat Exterior is specifically manufactured for the painter to repair and touch up exterior and interior surfaces, both new and old, prior to painting. It is designed for filling joints, hairline cracks etc. by hand application. Unlike conventional fillers, Handycoat Exterior has elastic properties, does not flake off, is permanent and retains its adhesion.

PROPERTIES

Handycoat Exterior is formulated using acrylic binders and precisely graded fillers. Properties include:

- Tough durable filler
- Weather resistant
- Alkali resistant
- Easy to apply
- Quick drying
- High crack resistance
- Excellent adhesion

AREAS OF USE

Handycoat Exterior is suitable for exterior as well as interior surfaces. When dry, Handycoat Exterior is weather resistant and bonds extremely well to cementitious materials, gypsum, gypsum boards, Sprayplaster and wood.

It is used as a thin coat filler for patching hairline cracks in walls, ceilings, soffits, repair to damaged plasterwork, paintwork, filling holes and defects in woodwork, making good to exposed concrete, filling of dents in galvanised and anti-rust primed metal.

PREPARATION OF SURFACE

Ensure dust, dirt, foreign matter are brushed away. Ridges and form oil should be removed.

When applying filler to old painted surfaces first wash down with soda / water solution, rinse and allow to dry before filling.

To stabilise a surface which shows signs of dusting or flaking, the use of Penetrating Primer is recommended.

APPLICATION & CLEANING OF TOOLS

Apply the filler in a thin, even layer; if the area under repair requires a thick coat, apply several thin layers, allowing each layer to dry before adding the next. Lightly sandpaper over the dry final surface before painting preferably within 9 hours of application.

Clean tools and equipment with water after use.

HEALTH & SAFETY

Avoid prolonged contact with eyes and skin. For detailed information refer to relevant material safety data sheet.

PACKAGING & STORAGE

Handycoat Exterior is supplied in 25kg and 5kg plastic containers.

Store containers in a clean dry area protected from direct sunlight and extreme heat and cold. Unopened containers can be stored for 18 months. Use oldest material first.

TERRACO offers a comprehensive range of products and services for most concrete and finishing needs. Please contact the TERRACO Technical Service Department or your local TERRACO agent for further information, samples, demonstrations and instructor services. The information given in this leaflet is based upon laboratory research, as well as extensive field work and application. All products are sold subject to standard conditions of sale which are available on request. This information is based on TERRACO's present state of knowledge and is intended to provide general information on TERRACO's products and their methods of use. The prospective user is recommended to determine the suitability of TERRACO's suggestions and products before adopting them on a commercial scale.

TECHNICAL DATA

Product	Ready mixed quick drying filler for exterior surfaces.
Binders	Styrene acrylate.
Fillers	Fine precisely graded fillers.
Dilution	With water if required.
Coverage	0.5 -1.5kg/m ² depending on substrate conditions.
Layer Thickness	Maximum 1mm.
Specific Gravity	1.65 +/- 0.05
Colour	White
Toxicity	Non-toxic.
Packaging	25kg and 5kg pails.
Storage	18 months in original unopened containers.

For technical enquiries please contact your nearest Terraco representative:

ALGERIA:

SARL Terraco Algeria
Tel: +213 (0)23 23 07 80
Fax: +213 (0)23 23 07 80
E-mail: terraco@terraco.dz
Web: www.terraco.dz

IRELAND:

Terraco Technical Centre, Ireland
Tel: +353 (0) 1 2819 045
Fax: +353 (0) 1 2819 048
E-mail: technical-centre@terraco.com
Web: www.terraco.com

TURKEY:

Terraco Yapi Malzemeleri Sanayi Ve Ticaret AS
Tel: +90 (0)222 236 0423
Fax: +90 (0)222 236 0425
E-mail: terraco@terraco.com.tr
Web: www.terraco.com.tr

CHINA:

Terraco Architectural Coatings China Co., Ltd.
Tel: +86 (0)20 8759 4742
Fax: +86 (0)20 8526 8056
E-mail: sales@terraco.com.cn
Web: www.terraco.com.cn

RUSSIA:

OOO Terraco Industry, Kirjach
Tel: +7 (0)495 9212 237
Fax: +7 (0)495 6273 881
E-mail: adm@terraco.ru
Web: www.terraco.ru

UAE:

Terraco UAE Ltd
Tel: +971 (0)4 326 2699
Fax: +971 (0)4 326 2733
E-mail: terraco@terraco.ae
Web: www.terraco.com

Terraco Chemical (Shanghai) Co., Ltd.

Tel: +86 (0)21 621020 48 / 18
Fax: +86 (0)21 625205 47
Email: sales@terraco.com.cn
Web: www.terraco.com.cn

OOO Terraco Vostok Ltd

Tel: +7 (0)4212 410563
Fax: +7 (0)4212 410591
E-mail: terracovostok@terraco.khv.ru
Web: www.terraco.com

UK:

ADDAGRIP
Tel: +44 (0)1825 761 333
Fax: +44 (0)1825 768 566
E-mail: sales@addagrip.co.uk
Web: www.addagrip.co.uk / www.terraco.com

EGYPT:

Terraco Egypt Chemical Industries S.A.E.
Tel: +20 (0)22 29184 53 / 57 / 58
Fax: +20 (0)22 29184 80
E-mail: terraco@terraco.com.eg
Web: www.terraco.com.eg

SOUTH KOREA:

Terraco Korea Co., Ltd
Tel: +82 (0) 2 5611 551
Fax: +82 (0)2 5671 771
E-mail: terraco@terraco.co.kr
Web: www.terraco.co.kr

VIETNAM:

Terraco Vietnam Co., Ltd
Tel: +84 (0)650 3 820 100
Fax: +84 (0)650 3 820101
E-mail: terraco@terraco.com.vn
Web: www.terraco.com

JORDAN:

Jordan Swedish Polymers Industrial Corp.
Tel: +962 (0)6 553 8751
Fax: +962 (0)6 553 6560
E-mail: terraco@nol.com.jo
Web: www.terraco.jo

THAILAND:

Terraco Industry (Thailand) Limited
Tel: +66 (0)2 946 68 56 / 58
Fax: +66 (0)2 946 68 59
E-mail: terraco@terraco.co.th
Web: www.terraco.com