

### OVERVIEW

Terraco Sprayplaster Finishcoat is an acrylic based, low VOC, ready to use compound of inert filler materials, for use on all common types of interior building surfaces. It gives a high quality, even surface for painting or other finishes. Terraco Sprayplaster Finishcoat is suitable for both precast and conventional buildings. It can be applied to either new or old solid surfaces of pre-cast or fair-faced concrete, sand/cement render, fair-faced and leveled brick work, etc. It is also used as a finish coat for Sprayplaster Basecoat/Basecoat DP. When used for finishing ceilings, the final coat may be left spray textured, in which case no further decoration is required. The finished Sprayplaster surface does not require priming before painting.

### PROPERTIES

TERRACO Sprayplaster Finishcoat is a ready to use compound, formulated from a selected blend of acrylic polymers and precisely graded fillers with the following properties:

- Low VOC
- Fire resistant (ASTM E-84 class-A)
- Easy to use
- Does not flake off
- High adhesion power
- High coverage
- Quick drying
- Vapour permeable

### AREA OF USE

For use on all non-wet areas requiring up to 2mm coat thickness. When used for finishing ceilings, the final coat may be left spray textured, in which case no further decoration is required. TERRACO Sprayplaster Finishcoat is suitable for both pre-cast and conventional buildings. It can be applied directly to either new or old solid surfaces of pre-cast or fair-faced concrete, sand/cement

### SURFACE PREPARATION

Ensure that dust, dirt and foreign matter are brushed away. Ridges and form oil must also be removed

### APPLICATION & CLEANING OF TOOLS

TERRACO Sprayplaster Finishcoat is applied over Terraco Sprayplaster Basecoat by spray or trowel. If dilution is required use 2-3% clean water. Apply 2 coats of Terraco Sprayplaster Finishcoat and level with a steel-edged spatula. The total thickness of Terraco Sprayplaster Finishcoat should not exceed 3 mm. Allow approx. 6-8 hours drying time between coats.

Clean tools and equipment with water after use. Drying time depends on site condition.

### HEALTH & SAFETY

Avoid prolonged contact with eyes and skin. For detailed information refer to relevant material safety data sheet.

### PACKAGING & STORAGE

Sprayplaster Finishcoat is supplied in 25kg plastic bags.

Store containers in a clean dry area protected from direct sunlight and extreme heat and cold. Unopened containers can be stored for 9 months. Use oldest material first.

TERRACO offers a comprehensive range of products and services for most concrete and finishing needs. Please contact the TERRACO Technical Service Department or your local TERRACO agent for further information, samples, demonstrations and instructor services. The information given in this leaflet is based upon laboratory research, as well as extensive field work and application. All products are sold subject to standard conditions of sale which are available on request. This information is based on TERRACO's present state of knowledge and is intended to provide general information on TERRACO's products and their methods of use. The prospective user is recommended to determine the suitability of TERRACO's suggestions and products before adopting them on a commercial scale.

#### TECHNICAL DATA

<b>Product</b>	Spray applied ready mixed plaster in paste form.
<b>Composition</b>	Formulated from acrylic binders and precisely graded fillers.
<b>Color</b>	Natural white
<b>PH Value</b>	8-9
<b>Specific Gravity</b>	1.78 ± 0.05
<b>Consumption Rate</b>	1.80 kg/m <sup>2</sup> /mm
<b>VOC</b>	< 5 g/L
<b>AL SA'FAT GBES</b>	Complies with AL SA'FAT GREEN BUILDING EVALUATION SYSTEM
<b>Fire Resistance</b>	ASTM E-84 Class-A
<b>Packaging</b>	25 kg Plastic bags
<b>Storage</b>	9 months in original unopened containers.

For technical enquiries please contact your nearest Terraco representative:

#### ALGERIA:

**SARL Terraco Algeria**  
Tel: +213 (0)23 23 07 80  
Fax: +213 (0)23 23 07 80  
E-mail: terraco@terraco.dz  
Web: www.terraco.dz

#### IRELAND:

**Terraco Technical Centre, Ireland**  
Tel: +353 (0) 1 2819 045  
Fax: +353 (0) 1 2819 048  
E-mail: technical-centre@terraco.com  
Web: www.terraco.com

#### THAILAND:

**Terraco Industry (Thailand) Limited**  
Tel: +66 (0)2 946 68 56 / 58  
Fax: +66 (0)2 946 68 59  
E-mail: terraco@terraco.co.th  
Web: www.terraco.com

#### CHINA:

**Terraco Architectural Coatings China Co., Ltd.**  
Tel: +86 (0)20 8759 4742  
Fax: +86 (0)20 8526 8056  
E-mail: sales@terraco.com.cn  
Web: www.terraco.com.cn

#### PAKISTAN:

**Terraco Pakistan Pvt. Ltd.**  
Tel: +92 (0)42 3529 70 56-8  
Fax: +92 (0)42 3529 70 55  
E-mail: terraco@terraco.pk  
Web: www.terraco.com

#### TURKEY:

**Terraco Yapi Malzemeleri Sanayi Ve Ticaret AS**  
Tel: +90 (0)222 236 0423  
Fax: +90 (0)222 236 0425  
E-mail: terraco@terraco.com.tr  
Web: www.terraco.com.tr

#### Terraco Chemical (Shanghai) Co., Ltd.

Tel: +86 (0)21 621020 48 / 18  
Fax: +86 (0)21 625205 47  
Email: sales@terraco.com.cn  
Web: www.terraco.com.cn

#### RUSSIA:

**OOO Terraco Industry, Kirjach**  
Tel: +7 (0)495 9212 237  
Fax: +7 (0)495 6273 881  
E-mail: adm@terraco.ru  
Web: www.terraco.ru

#### UAE:

**Terraco UAE Ltd**  
Tel: +971 (0)4 326 2699  
Fax: +971 (0)4 326 2733  
E-mail: terraco@terraco.ae  
Web: www.terraco.com

#### EGYPT:

**Terraco Egypt Chemical Industries S.A.E.**  
Tel: +20 (0)22 29184 53 / 57 / 58  
Fax: +20 (0)22 29184 80  
E-mail: terraco@terraco.com.eg  
Web: www.terraco.com.eg

#### OOO Terraco Vostok Ltd

Tel: +7 (0)4212 410563  
Fax: +7 (0)4212 410591  
E-mail: terracovostok@terraco.khv.ru  
Web: www.terraco.com

#### UK:

**ADDAGRIP**  
Tel: +44 (0)1825 761 333  
Fax: +44 (0)1825 768 566  
E-mail: sales@addagrip.co.uk  
Web: www.addagrip.co.uk / www.terraco.com

#### JORDAN:

**Jordan Swedish Polymers Industrial Corp.**  
Tel: +962 (0)6 553 8751  
Fax: +962 (0)6 553 6560  
E-mail: terraco@nol.com.jo  
Web: www.terraco.jo

#### SOUTH KOREA:

**Terraco Korea Co., Ltd**  
Tel: +82 (0) 2 5611 551  
Fax: +82 (0)2 5671 771  
E-mail: terraco@terraco.co.kr  
Web: www.terraco.co.kr

#### VIETNAM:

**Terraco Vietnam Co., Ltd**  
Tel: +84 (0)650 3 820 100  
Fax: +84 (0)650 3 820101  
E-mail: terraco@terraco.com.vn  
Web: www.terraco.com