

OVERVIEW

Stucco Vintage T200 is a decorative mineral floor finish designed for interior application to give the appearance of a natural cast concrete floor. It is easy to apply and has excellent strength, abrasion resistance and durability. A range of attractive patterns can be achieved depending on application tools and installation method. It is finished with a clear resin-based epoxy topcoat or water based acrylic topcoat resulting in an attractive sheen which is easy to maintain.

PROPERTIES

Stucco Vintage T200 has the following properties:

- Faux concrete finish
- Easy to apply
- Excellent adhesion
- Excellent durability
- High abrasion resistance
- Low VOC system
- Water and stain resistance after application of Stucco Vintage Clear Coat

AREAS OF USE

Stucco Vintage T200 is used for application on commercial floors such as offices, restaurants, shops and department stores.

PREPARATION OF SURFACE

Concrete floors should be fully cured for 3-4 weeks. Ensure that all dust, dirt and foreign matter are scraped and brushed away. All cracks, chips, voids and damages should be repaired first.

PRIMING

Apply Terrabond-A (1:5 diluted with clean water) or Terraco Penetrating Primer Clear as a primer prior to application of Stucco Vintage T200. On extremely absorbent, porous surfaces or under extreme climatic conditions, apply 2-3 coats of primer.

MIXING

Add powder to resin and mix using a drill agitator for 3 minutes to get lump free paste form. Mixed material should be used within 40 minutes of mixing. Do not re-temper material with extra water.

APPLICATION & CLEANING OF TOOLS

Stucco Vintage T200 is applied with steel trowel in 2 coats. Apply first coat of 1.5 to 2 mm, allow to dry for 6 to 8 hours & sand the surface with 120 grit fine sandpaper. Apply second coat of 1- 1.5 mm with trowel & allow to dry for 6 to 10 hours. Sand the final finish with 120 grit fine sandpaper to get various patterns. Apply clear coat after 8 to 10 hours.

Stucco Vintage clear coat application: Stucco Vintage clear coat is available in two gloss levels High gloss (HG) & Low gloss (LG). For high gloss level used Epirok TC (solvent free epoxy clear coat) as topcoat. For low gloss finish, apply Diamond Seal (water based acrylic clear coat) as topcoat.

Clean tools and equipment with water immediately after use.

HEALTH & SAFETY

Avoid prolonged contact with eyes and skin. For detailed information refer to relevant material safety data sheet.

PACKAGING & STORAGE

Stucco Vintage T200 is supplied in 20kg kit as a 2k system (16.9 kg powder and 3.1 kg resin).

Store containers in a clean dry area protected from direct sunlight and extreme heat and cold. Unopened containers can be stored for 6 months. Use oldest material first.

TERRACO offers a comprehensive range of products and services for most concrete and finishing needs. Please contact the TERRACO Technical Service Department or your local TERRACO agent for further information, samples, demonstrations and instructor services. The information given in this leaflet is based upon laboratory research, as well as extensive field work and application. All products are sold subject to standard conditions of sale which are available on request. This information is based on TERRACO's present state of knowledge and is intended to provide general information on TERRACO's products and their methods of use. The prospective user is recommended to determine the suitability of TERRACO's suggestions and products before adopting them on a commercial scale.

TECHNICAL DATA

Product	Decorative mineral floor finish.
Binder	Hydraulic and organic binders.
Additives	Plasticizing agents, adhesion promoters and water retention agents.
Colours	Available in standard range of 6 colours as per Stucco Vintage Catalogue.
Thickness of Layer	3 to 3.5 mm
Consumption	1.5 kg/m ² per 1mm thickness
Mixing Ratio	16.9 kg powder to 3.1 kg resin
Compressive Strength	>5 N/mm ²
Adhesion Strength	>0.25 N/mm ²
Packaging	20 kg plastic pail (16,9 kg powder in paper bags & 3.1 kg resin in jerrycan)
Storage	6 months in original unopened container.

For technical enquiries please contact your nearest Terraco representative:

ALGERIA:

SARL Terraco Algeria
Tel: +213 (0)23 23 07 80
Fax: +213 (0)23 23 07 80
E-mail: terraco@terraco.dz
Web: www.terraco.dz

IRELAND:

Terraco Technical Centre, Ireland
Tel: +353 (0) 1 2819 045
Fax: +353 (0) 1 2819 048
E-mail: technical-centre@terraco.com
Web: www.terraco.com

TURKEY:

Terraco Yapi Malzemeleri Sanayi Ve Ticaret AS
Tel: +90 (0)222 236 0423
Fax: +90 (0)222 236 0425
E-mail: terraco@terraco.com.tr
Web: www.terraco.com.tr

CHINA:

Terraco Architectural Coatings China Co., Ltd.
Tel: +86 (0)20 8759 4742
Fax: +86 (0)20 8526 8056
E-mail: sales@terraco.com.cn
Web: www.terraco.com.cn

RUSSIA:

OOO Terraco Industry, Kirjach
Tel: +7 (0)495 9212 237
Fax: +7 (0)495 6273 881
E-mail: adm@terraco.ru
Web: www.terraco.ru

UAE:

Terraco UAE Ltd
Tel: +971 (0)4 326 2699
Fax: +971 (0)4 326 2733
E-mail: terraco@terraco.ae
Web: www.terraco.com

Terraco Chemical (Shanghai) Co., Ltd.

Tel: +86 (0)21 621020 48 / 18
Fax: +86 (0)21 625205 47
Email: sales@terraco.com.cn
Web: www.terraco.com.cn

OOO Terraco Vostok Ltd

Tel: +7 (0)4212 410563
Fax: +7 (0)4212 410591
E-mail: terracovostok@terrakovostok.ru
Web: www.terraco.com

UK:

ADDAGRIP
Tel: +44 (0)1825 761 333
Fax: +44 (0)1825 768 566
E-mail: sales@addagrip.co.uk
Web: www.addagrip.co.uk / www.terraco.com

EGYPT:

Terraco Egypt Chemical Industries S.A.E.
Tel: +20 (0)22 29184 53 / 57 / 58
Fax: +20 (0)22 29184 80
E-mail: terraco@terraco.com.eg
Web: www.terraco.com.eg

SOUTH KOREA:

Terraco Korea Co., Ltd
Tel: +82 (0) 2 5611 551
Fax: +82 (0)2 5671 771
E-mail: terraco@terraco.co.kr
Web: www.terraco.co.kr

VIETNAM:

Terraco Vietnam Co., Ltd
Tel: +84 (0)650 3 820 100
Fax: +84 (0)650 3 820101
E-mail: terraco@terraco.com.vn
Web: www.terraco.com

JORDAN:

Jordan Swedish Polymers Industrial Corp.
Tel: +962 (0)6 553 8751
Fax: +962 (0)6 553 6560
E-mail: terraco@nol.com.jo
Web: www.terraco.jo

THAILAND:

Terraco Industry (Thailand) Limited
Tel: +66 (0)2 946 68 56 / 58
Fax: +66 (0)2 946 68 59
E-mail: terraco@terraco.co.th
Web: www.terraco.com