

Flexible polymer modified pigmented cementitious waterproof coating

| Crack Bridging and Elastomeric Formulation

| For Exposed and Concealed Application

Weathercoat™ Hydra

ويذر كوت™ هايدرا

3K Pigmented Cementitious Flexible Waterproofing Kit



FLEXIBILITY



CO2 BARRIER



BREATHABLE



UV RESISTANT



POSITIVE PRESSURE

AREAS OF USE

- Decorative elements exposed to water sources like fountains
- Concrete flat roof (exposed and under tile application)
- Drywall construction - wet areas

أماكن الاستخدام

- الديكورات المكشوفة للمياه مثل النوافير
- الاسطح الاسمنتية (تطبق مكشوفة أو تحت البلاط)
- الاماكن الرطبة لمناطق جدران الجبس

* Water Test - After 7 days of application

MATERIAL CONSUMPTION

2.8 - 3.8 kg/m² (Mixed)
Total thickness: 1.5 - 2.0mm
Coats: 2 - 3 coats
(Min. 0.75mm/coat
Max. 1.0mm/coat)

استهلاك المواد

كيلوغرام لكل متر مربع ٢.٨ - ٣.٨
(مكسيكرت مختلط)
السماكة الكلية: ٢.٠ مم - ١.٥ مم
(للاستخدام تحت البلاط: ١.٤ إلى ١.٦ مم
وللمناطق المكشوفة: ١.٨ إلى ٢.٠ مم
يوصى بسمك التطبيق)

TOOLS



Brush



Spray



Roller

COLOUR RANGE



Standard Kit:
10kg Powder + 5kg Resin + Colourant