///// TERRACO



www.terraco.com

SWEDEN • UK • IRELAND • RUSSIA • TURKEY • ALGERIA • EGYPT JORDAN • UAE • THAILAND • VIETNAM • CHINA • KOREA



ERRAVERTINE





ERRAVERTINE

NATURAL POLISHED INTERNAL PLASTER

Terravertine natural polished plaster is one of the unique Terraco Designer Collection products formulated using modern technology to create the sophisticated Italian marmorino stucco effect which can be dated back to Roman times. A combination of smooth and textured finish, applied in panels, provides for a dramatic and elegant finish. Terravertine is available in natural earth tone shade using convertional shades of natural colourant paste.



FEATURES AND BENEFITS

- Smooth and / or textured polished finish
- » Highly resistant to staining and scratching
- » Non combustible
- » Environmentally friendly, Low VOC
- » Areas of use: interior substrates concrete, cement rendering, lightweight concrete, fair-faced block-work, gypsum drywall.

TERRAVERTINE









Colour: TVT-101 (Smooth Finish)



Colour: TVT-103 (Texture Finish)

| Product Details: | Terravertine Finishcoat | Tex Primer Aggregate |
|-----------------------|--|--|
| Description: | Limed based plaster, powder form. | White or tinted, liquid form. |
| Material Consumption: | 1.5-2kg/m ² | 6–8 m²/litre |
| Mixing Ratio: | 15kg powder: 5.5 ltr to 6.5 ltr water. | Ready to use. |
| Compressive Strength: | 2.0 N/mm ² | Not applicable. |
| Tools Used: | Trowel | Rrush Brush |
| Storage: | 12 months in original unopened pails. | 12 months in original unopened containers. |
| Package: | 15 kg paper bags/pails for Finishcoat. | 3.6 ltr and 18 ltr pails. |
| Application Method: | Apply 1 coat of Terraco Tex Primer Aggregate. Apply 2 coats of Terraco Terravertine Finishcoat using white steel fine-edged trowel and finish with desired method, either smooth or texture finish. | |









Please note:

As the Terravertine product range is formulated using a combination of natural raw materials, colour variances may occur. Should you wish to minimise these colour differences, it is recommended that the applicator uses products from the same batch. Deep shades in cementitious dry powder products results in patchy look due to blooming effect when it is applied smooth & levelled. Inconsistency in water content & mixing time are also contributing factor for colour variation.

Technical Data Sheets and Material Safety Data Sheets are available from your Terraco representative or on www.terraco.com. Although every precaution has been taken to ensure the accuracy of the colours and textures represented herein they should be considered indicative. Products containing natural aggregates may be susceptible to colour variation and we recommend that you order sufficient quantity for the complete project at one time. Terraco does not warrant the accuracy of the information provided herein and all information is subject to change without notice. © All rights reserved. Terraco Holdings Ltd.