

OVERVIEW

Acrylic Crack Filler is a ready to use flexible crack filler recommended to be used on all common building surfaces. It is specially manufactured for the painter to repair and touch-up exterior and interior surfaces. It is designed for filling joints, hairline cracks etc. Unlike conventional fillers, Acrylic Crack Filler has elastic properties, does not flake off, is permanent and retains its adhesion.

PROPERTIES

- Easy to apply
- Excellent adhesion
- Excellent impact resistance
- Highly flexible

AREAS OF USE

Acrylic Crack Filler is suitable for exterior as well as interior surfaces. When dry, Acrylic Crack Filler is weather resistant and bonds extremely well to cementitious materials, gypsum, gypsum boards, sprayplaster, wood, galvanized and primed anti-rust steel surfaces, etc.

PREPARATION OF SURFACE

Ensure the substrate is sound. Using a putty knife, cut along the cracks in a V shape. The maximum openings of the cracks should be 5 mm wide x 3 mm deep. Remove all the dust, dirt, foreign matter, plaster debris, etc. from the surface completely. Apply a diluted coat of Terraco Terrabond A (1:5 with water) to the opened crack by brush.

APPLICATION & CLEANING OF TOOLS

Infill the crack-openings using Terraco Acrylic Crack Filler and allow to dry. Ensure the crack filling is done in a crisscross pattern. Allow to dry for 6-8 hours and apply a second coat (if necessary) to achieve full levelling. If required, lightly sand down the final surface before painting, preferably within 24 hours of application. Apply the filler in a thin even layer (maximum 1mm).

Clean tools and equipment with water after use.

LIMITATIONS

Do not apply during rising temperatures to avoid the risk of out gassing resulting in pin-holing. Do not apply on bituminous coating. For exterior areas, do not apply if rain is likely over the next 24 hours.

HEALTH & SAFETY

Avoid prolonged contact with eyes and skin. For detailed information refer to relevant material safety data sheet.

PACKAGING & STORAGE

Acrylic Crack Filler is supplied in 1kg, 5kg and 25kg plastic pails.

Store containers in a clean dry area protected from direct sunlight and extreme heat and cold. Do not allow material to freeze. Unopened containers can be stored for 12 months. Use oldest material first.

TERRACO offers a comprehensive range of products and services for most concrete and finishing needs. Please contact the TERRACO Technical Service Department or your local TERRACO agent for further information, samples, demonstrations and instructor services. The information given in this leaflet is based upon laboratory research, as well as extensive field work and application. All products are sold subject to standard conditions of sale which are available on request. This information is based on TERRACO's present state of knowledge and is intended to provide general information on TERRACO's products and their methods of use. The prospective user is recommended to determine the suitability of TERRACO's suggestions and products before adopting them on a commercial scale.

TECHNICAL DATA

Product Ready mixed crack filler for common building substrates.

Binders Acrylic copolymer.

Fillers Fine precisely graded fillers.

Dilution With water, if required.

Coverage 0.5 – 1.5 kg/m² depending on substrate conditions.

Layer Thickness Maximum 1 mm.

Specific Gravity 1.70 ± 0.05

Colour Natural White.

Packaging 1kg, 5kg and 25kg plastic pails

Storage 12 months in original unopened containers.

For technical enquiries please contact your nearest Terraco representative:

CHINA:

Terraco Architectural Coatings China Co., Ltd.

Tel: +86 (0)20 8759 4742
Fax: +86 (0)20 8526 8056
E-mail: sales@terraco.com.cn
Web: www.terraco.com.cn

Terraco Chemical (Shanghai) Co., Ltd.

Tel: +86 (0)21 621020 48 / 18
Fax: +86 (0)21 625205 47
Email: sales@terraco.com.cn
Web: www.terraco.com.cn

EGYPT:

Terraco Egypt Chemical Industries S.A.E.

Tel: +20 (0)22 29184 53 / 57 / 58
Fax: +20 (0)22 29184 80
E-mail: terraco@terraco.com.eg
Web: www.terraco.com.eg

JORDAN:

Jordan Swedish Polymers Industrial Corp.

Tel: +962 (0)6 553 8751
Fax: +962 (0)6 553 6560
E-mail: terraco@nol.com.jo
Web: www.terraco.jo

IRELAND:

Terraco Technical Centre, Ireland

Tel: +353 (0) 1 2819 045
Fax: +353 (0) 1 2819 048
E-mail: technical-centre@terraco.com
Web: www.terraco.com

PAKISTAN:

Terraco Pakistan Pvt. Ltd.

Tel: +92 (0)42 3529 70 56-8
Fax: +92 (0)42 3529 70 55
Email: terraco@terraco.pk
Web: www.terraco.com

RUSSIA:

OOO Terraco Sweden Ltd, Russia

Tel: +7 (0)495 9212 237
Fax: +7 (0)495 6273 881
E-mail: adm@terraco.ru
Web: www.terraco.ru

OOO Terraco Vostok Ltd

Tel: +7 (0)4212 410563
Fax: +7 (0)4212 410591
E-mail: terracovostok@terrakovostok.ru
Web: www.terraco.com

SOUTH KOREA:

Terraco Korea Co., Ltd

Tel: +82 (0) 2 5611 551
Fax: +82 (0)2 5671 771
E-mail: terraco@terraco.co.kr
Web: www.terraco.co.kr

THAILAND:

Terraco Industry (Thailand) Limited

Tel: +66 (0)2 946 68 56 / 58
Fax: +66 (0)2 946 68 59
E-mail: terraco@terraco.co.th
Web: www.terraco.com

TURKEY:

Terraco Yapi Malzemeleri Sanayi Ve Ticaret AS

Tel: +90 (0)222 236 0423
Fax: +90 (0)222 236 0425
E-mail: terraco@terraco.com.tr
Web: www.terraco.com.tr

UAE:

Terraco UAE Ltd

Tel: +971 (0)4 326 2699
Fax: +971 (0)4 326 2733
E-mail: terraco@terraco.ae
Web: www.terraco.com

UK:

ADDAGRIP

Tel: +44 (0)1825 761 333
Fax: +44 (0)1825 768 566
E-mail: sales@addagrip.co.uk
Web: www.addagrip.co.uk / www.terraco.com

VIETNAM:

Terraco Vietnam Co., Ltd

Tel: +84 (0)650 3 820 100
Fax: +84 (0)650 3 820101
E-mail: terraco@terraco.com.vn
Web: www.terraco.com