

### OVERVIEW

Handycoat Interior Stucco Putty is a ready to use filler and skim-coat for most building surfaces, including sand / cement render and gypsum board. It has an extra fine particle size to give a high quality even surface for painting. Handycoat Interior Stucco Putty is specially manufactured for the painter to repair and touch up interior surfaces, both old and new, prior to painting.

### PROPERTIES

Handycoat Interior Stucco Putty is made from a selected blend of acrylic polymers and precisely graded fillers. The product is:

- Easy to use.
- Does not flake off.
- Has high adhesion power.
- Has high coverage.
- Quick drying.
- Vapour permeable

### AREAS OF USE

When dry, Handycoat Interior Stucco Putty bonds extremely well to cementitious materials, gypsum, gypsum boards, sprayplasters, wood and all common building surfaces. Handycoat Interior Stucco Putty is suitable for skimming over other Handycoat / Sprayplaster grades to produce an extra fine surface for fine finishing.

### PREPARATION OF SURFACE

Ensure that dust, dirt and foreign matter are brushed away. Ridges and form oil must also be removed. The use of TERRACO P Primer is recommended on dusting or flaking surfaces.

### APPLICATION & CLEANING OF TOOLS

Apply the filler in a thin even layer. Apply two or more coats if necessary, allowing to dry between layers. Lightly sand down the final surface before painting, preferably within 24 hours of application.

Clean tools and equipment with water after use.

### HEALTH & SAFETY

Avoid prolonged contact with eyes and skin. For detailed information refer to relevant material safety data sheet.

### PACKAGING & STORAGE

Handycoat Interior Stucco Putty is supplied in 1 kg cup, 5 kg and 18 ltr plastic pails.

Store containers in a clean dry area protected from direct sunlight and extreme heat and cold. Do not allow material to freeze. Unopened containers can be stored for 12 months. Use oldest material first

TERRACO offers a comprehensive range of products and services for most concrete and finishing needs. Please contact the TERRACO Technical Service Department or your local TERRACO agent for further information, samples, demonstrations and instructor services. The information given in this leaflet is based upon laboratory research, as well as extensive field work and application. All products are sold subject to standard conditions of sale which are available on request. This information is based on TERRACO's present state of knowledge and is intended to provide general information on TERRACO's products and their methods of use. The prospective user is recommended to determine the suitability of TERRACO's suggestions and products before adopting them on a commercial scale.

## TECHNICAL DATA

<b>Product</b>	Ready mixed quick drying filler for interior surfaces.
<b>Binders</b>	Acrylic copolymer.
<b>Fillers</b>	Fine precisely graded fillers.
<b>Dilution</b>	With water if required.
<b>Coverage</b>	0.2 -0.4kg/m <sup>2</sup> depending on substrate conditions.
<b>Layer Thickness</b>	Maximum 1mm.
<b>Specific Gravity</b>	1.75 ± 0.05
<b>Colour</b>	White.
<b>Durability</b>	Negligible shrinkage.
<b>Toxicity</b>	Non-toxic.
<b>Packaging</b>	1 kg cup, 5kg and 18 ltr plastic pails.
<b>Storage</b>	12 month in original unopened containers.

For technical enquiries please contact your nearest Terraco representative:

### ALGERIA:

**SARL Terraco Algeria**

Tel: +213 (0)23 23 07 80  
Fax: +213 (0)23 23 07 80  
E-mail: terraco@terraco.dz  
Web: www.terraco.dz

### IRELAND:

**Terraco Technical Centre, Ireland**

Tel: +353 (0) 1 2819 045  
Fax: +353 (0) 1 2819 048  
E-mail: technical-centre@terraco.com  
Web: www.terraco.com

### TURKEY:

**Terraco Yapi Malzemeleri Sanayi Ve Ticaret AS**

Tel: +90 (0)222 236 0423  
Fax: +90 (0)222 236 0425  
E-mail: terraco@terraco.com.tr  
Web: www.terraco.com.tr

### CHINA:

**Terraco Architectural Coatings China Co., Ltd.**

Tel: +86 (0)20 8759 4742  
Fax: +86 (0)20 8526 8056  
E-mail: sales@terraco.com.cn  
Web: www.terraco.com.cn

### RUSSIA:

**OOO Terraco Industry, Kirjach**

Tel: +7 (0)495 9212 237  
Fax: +7 (0)495 6273 881  
E-mail: adm@terraco.ru  
Web: www.terraco.ru

### UAE:

**Terraco UAE Ltd**

Tel: +971 (0)4 326 2699  
Fax: +971 (0)4 326 2733  
E-mail: terraco@terraco.ae  
Web: www.terraco.com

**Terraco Chemical (Shanghai) Co., Ltd.**

Tel: +86 (0)21 621020 48 / 18  
Fax: +86 (0)21 625205 47  
Email: sales@terraco.com.cn  
Web: www.terraco.com.cn

**OOO Terraco Vostok Ltd**

Tel: +7 (0)4212 410563  
Fax: +7 (0)4212 410591  
E-mail: terracovostok@terraco.kv.ru  
Web: www.terraco.com

### UK:

**ADDAGRIP**

Tel: +44 (0)1825 761 333  
Fax: +44 (0)1825 768 566  
E-mail: sales@addagrip.co.uk  
Web: www.addagrip.co.uk / www.terraco.com

### EGYPT:

**Terraco Egypt Chemical Industries S.A.E.**

Tel: +20 (0)22 29184 53 / 57 / 58  
Fax: +20 (0)22 29184 80  
E-mail: terraco@terraco.com.eg  
Web: www.terraco.com.eg

### SOUTH KOREA:

**Terraco Korea Co., Ltd**

Tel: +82 (0) 2 5611 551  
Fax: +82 (0)2 5671 771  
E-mail: terraco@terraco.co.kr  
Web: www.terraco.co.kr

### VIETNAM:

**Terraco Vietnam Co., Ltd**

Tel: +84 (0)650 3 820 100  
Fax: +84 (0)650 3 820101  
E-mail: terraco@terraco.com.vn  
Web: www.terraco.com

### JORDAN:

**Jordan Swedish Polymers Industrial Corp.**

Tel: +962 (0)6 553 8751  
Fax: +962 (0)6 553 6560  
E-mail: terraco@nol.com.jo  
Web: www.terraco.jo

### THAILAND:

**Terraco Industry (Thailand) Limited**

Tel: +66 (0)2 946 68 56 / 58  
Fax: +66 (0)2 946 68 59  
E-mail: terraco@terraco.co.th  
Web: www.terraco.com