# IIIII TERRACO

# SPRAYPLASTER FINISHCOAT SPRAY APPLIED READYMIXED PLASTER 63410

# OVERVIEW

Terraco Sprayplaster Finishcoat is an acrylic based, low VOC, ready to use compound of inert filler materials, for use on all common types of interior building surfaces. It gives a high quality, even surface for painting or other finishes. Terraco Sprayplaster Finishcoat is suitable for both precast and conventional buildings. It can be applied to either new or old solid surfaces of pre-cast or fair-faced concrete, sand/cement render, fair-faced and leveled brick work, etc. It is also used as a finish coat for Sprayplaster Basecoat/Basecoat DP. When used for finishing ceilings, the final coat may be left spray textured, in which case no further decoration is required. The finished Sprayplaster surface does not require priming before painting.

# PROPERTIES

TERRACO Sprayplaster Finishcoat is a ready to use compound, formulated from a selected blend of acrylic polymers and precisely graded fillers with the following properties:

- Low VOC
- Fire resistant (ASTM E-84 class-A)
- Easy to use
- Does not flake off
- High adhesion power
- High coverage
- Quick drying
- Vapour permeable

# AREA OF USE

For use on all non-wet areas requiring up to 2mm coat thickness. When used for finishing ceilings, the final coat may be left spray textured, in which case no further decoration is required. TERRACO Sprayplaster Finishcoat is suitable for both pre-cast and conventional buildings. It can be applied directly to either new or old solid surfaces of pre-cast or fair-faced concrete, sand/cement

### SURFACE PREPARATION

Ensure that dust, dirt and foreign matter are brushed away. Ridges and form oil must also be removed

# APPLICATION & CLEANING OF TOOLS

TERRACO Sprayplaster Finishcoat is applied over Terraco Sprayplaster Basecoat by spray or trowel. If dilution is required use 2-3% clean water. Apply 2 coats of Terraco Sprayplaster Finishcoat and level with a steel-edged spatula. The total thickness of Terraco Sprayplaster Finishcoat should not exceed 3 mm. Allow approx. 6-8 hours drying time between coats.

Clean tools and equipment with water after use. Drying time depends on site condition.

### HEALTH & SAFETY

Avoid prolonged contact with eyes and skin. For detailed information refer to relevant material safety data sheet.

# PACKAGING & STORAGE

Sprayplaster Finishcoat is supplied in 25kg plastic bags.

Store containers in a clean dry area protected from direct sunlight and extreme heat and cold. Unopened containers can be stored for 9 months. Use oldest material first.

TERRACO offers a comprehensive range of products and services for most concrete and finishing needs. Please contact the TERRACO Technical Service Department or your local TERRACO agent for further information, samples, demonstrations and instructor services. The information given in this leaflet is based upon laboratory research, as well as extensive field work and application. All products are sold subject to standard conditions of sale which are available on request. This information is based on TERRACO's present state of knowledge and is intended to provide general information on TERRACO's products and their methods of use. The prospective user is recommended to determine the suitability of TERRACO's suggestions and products before adopting them on a commercial scale.

# IIIII TERRACO

# **TECHNICAL DATA**

Product	Spray applied ready mixed plaster in paste form.
Composition	Formulated from acrylic binders and precisely graded fillers.
Color	Natural white
PH Value	8-9
Specific Gravity	$1.78 \pm 0.05$
Consumption Rate	1.80 kg/m²/mm
VOC	< 5 g/L
AL SA'FAT GBES	Complies with AL SA'FAT GREEN BUILDING EVALUATION SYSTEM
Fire Resistance	ASTM E-84 Class-A
Packaging	25 kg Plastic bags
Storage	9 months in original unopened containers.

For technical enquiries please contact your nearest Terraco representative:

#### ALGERIA:

**SARL Terraco Algeria** Tel: +213 (0)23 23 07 80 Fax: +213 (0)23 23 07 80 E-mail: terraco@terraco.dz Web: www.terraco.dz

#### CHINA:

**Terraco Architectural Coatings China Co., Ltd.** Tel: +86 (0)20 8759 4742 Fax: +86 (0)20 8526 8056 E-mail: sales@terraco.com.cn Web: www.terraco.com.cn

#### Terraco Chemical (Shanghai) Co., Ltd.

Tel: +86 (0)21 621020 48 / 18 Fax: +86 (0)21 625205 47 Email: sales@terraco.com.cn Web: www.terraco.com.cn

#### EGYPT:

**Terraco Egypt Chemical Industries S.A.E.** Tel: +20 (0)22 29184 53 / 57 / 58 Fax: +20 (0)22 29184 80 E-mail: terraco@terraco.com.eg Web: www.terraco.com.eg

#### JORDAN:

Jordan Swedish Polymers Industrial Corp. Tel: +962 (0)6 553 8751 Fax: +962 (0)6 553 6560 E-mail: terraco@nol.com.jo Web: www.terraco.jo

#### IRELAND:

Terraco Technical Centre, Ireland Tel: +353 (0) 1 2819 045

Fax : +353 (0) 1 2819 048 E-mail: technical-centre@terraco.com Web: www.terraco.com

#### PAKISTAN:

**Terraco Pakistan Pvt. Ltd.** Tel: +92 (0)42 3529 70 56-8 Fax: +92 (0)42 3529 70 55 Email: terraco@terraco.pk Web: www.terraco.com

#### RUSSIA:

**OOO Terraco Industry, Kirjach** Tel: +7 (0)495 9212 237

Fax: +7 (0)495 6273 881 E-mail: adm@terraco.ru Web: www.terraco.ru

#### 000 Terraco Vostok Ltd

Tel: +7 (0)4212 410563 Fax: +7 (0)4212 410591 E-mail: terracovostok@terracokhv.ru Web: www.terraco.com

#### SOUTH KOREA:

Terraco Korea Co., Ltd Tel: +82 (0) 2 5611 551 Fax: +82 (0)2 5671 771 E-mail: terraco@terraco.co.kr Web: www.terraco.co.kr

#### THAILAND:

**Terraco Industry (Thailand) Limited** Tel: +66 (0)2 946 68 56 / 58 Fax: +66 (0)2 946 68 59 E-mail: terraco@terraco.co.th Web: www.terraco.com

#### TURKEY:

**Terraco Yapi Malzemeleri Sanayi Ve Ticaret AS** Tel: +90 (0)222 236 0423 Fax: +90 (0)222 236 0425 E-mail: terraco@terraco.com.tr Web: www.terraco.com.tr

#### UAE:

**Terraco UAE Ltd** Tel: +971 (0)4 326 2699 Fax: +971 (0)4 326 2733 E-mail: terraco@terraco.ae Web: www.terraco.com

#### UK: ADDAGRIP

Tel: +44 (0)1825 761 333 Fax: +44 (0)1825 768 566 E-mail: sales@addagrip.co.uk Web: www.addagrip.co.uk / www,terraco.com

#### VIETNAM:

**Terraco Vietnam Co., Ltd** Tel: +84 (0)650 3 820 100 Fax: +84 (0)650 3 820101 E-mail: terraco@terraco.com.vn Web: www.terraco.com