

OVERVIEW

Terralite Trustone is a stone effect exterior coating based on pure acrylic polymers and mineral aggregate. It is applied by spray to achieve a hammer finish granite effect which is extremely authentic. It is available in a range of attractive finishes and three different textures:

Picco (fine), Medio (medium) and Grande (coarse).

PRODUCT GRADES/CODES

Picco	61365
Grande	61366
Medio	61367

PROPERTIES

Terralite Trustone is formulated from selected fillers, dispersed in an acrylic binder, and supplied ready for use in a paste form. After application and over coating with Trustone clear coat, it becomes highly weather resistant, washable and abrasion resistant. It provides an excellent protective coating, with high resistance to atmospheric corrosion and fading.

ADVANTAGES

- High water and weather resistant
- Washable
- Abrasion resistant
- Highly decorative finish

AREAS OF USE

Exterior and interior facades of concrete, cement rendering and wood, on commercial and industrial complexes, housing complexes and is particularly effective in areas of severe climatic exposure

PREPARATION OF SURFACE

New surfaces: Ensure that all dust, dirt and foreign matter are brushed and scraped away. Also ensure the surfaces are free from salts, oil, grease and ridges. Protect all adjacent surfaces not to be covered. All cracks, chips, voids and damages should be repaired with Terraco Handycoat Exterior.

Old surfaces: Before applying Terralite Trustone to old surfaces, ensure the substrate is firm. First wash down the surface with a soda/water solution, rinse and allow to dry before repairing or applying the first coat.

Prime surfaces with a coat of Terraco Penetrating Primer or Terraco Terrabond A solution (1:5) prior to application of Terralite Trustone.

APPLICATION & CLEANING OF TOOLS

Application Condition:

Do not apply above 40° C or below 5° C. Do not apply if rain is expected within 24 hours of application. To unify the substrate colour, apply two coats of Terraco Terralite Undercoat by spray/roller at a rate of 300 gm/m² for two coats application. Allow to dry for 4 hours before applying Terralite Trustone.

Terralite Trustone is applied by hopper gun to create a hammer finish or lightly knocked down with a trowel to produce a pitted look as per approved finish. Apply 1st coat of Terraco Terralite Trustone at rate of 1.5 – 2 kg/m², allow to partially set and apply wet-on-wet 2nd coat of Terraco Terralite Trustone at rate of 1 – 1.5 kg/m². Allow to dry for 24 hours. Feed of material and pressure to the hopper gun should be regulated as per required finish.

Apply two coats of Terralite Glaze-Coat by spray / roller (preferably by spray application) at a rate of 150 - 200 gm/m² for two coat application. Application of Terralite Glaze-Coat should be uniform to avoid any visual surface unevenness.

Cleaning of tools:

Tools and equipment should be cleaned with water immediately after use.

HEALTH & SAFETY

Avoid prolonged contact with eyes and skin. For detailed information refer to relevant material safety data sheet.

PACKAGING & STORAGE

Terralite Trustone is supplied in 23kg plastic pails.

Store containers in a clean dry area protected from direct sunlight and extreme heat and cold. Unopened containers can be stored for 12 months. Use oldest material first.

TECHNICAL DATA

Product	Stone effect exterior coating.	
Binders	Pure acrylic.	
Fillers	Precisely graded filler.	
Colour	Available in a range of colours (refer to Trustone catalogue).	
Specific Gravity	1.65 ± 0.05	
Fire Resistance	ASTM E-84 Class-A	
AL SA'FAT GBES	Complies with AL SA'FAT GREEN BUILDING EVALUATION SYSTEM requirements	
Material Consumption	Picco:	3.0-3.5 kg/m ²
	Medio:	3.0-3.5 kg/m ²
	Grande:	3.0-3.5 kg/m ²
Application	Spray application with hopper gun. (Nozzle size depends on spray texture)	
	Picco:	3 - 6 mm nozzle
	Medio:	4 - 6 mm nozzle
	Grande:	4 - 6 mm nozzle
Packaging	23kg plastic pail	
Storage	12 months in original unopened packs.	

TERRACO offers a comprehensive range of products and services for most concrete and finishing needs. Please contact the TERRACO Technical Service Department or your local TERRACO agent for further information, samples, demonstrations and instructor services. The information given in this leaflet is based upon laboratory research, as well as extensive field work and application. All products are sold subject to standard conditions of sale which are available on request. This information is based on TERRACO's present state of knowledge and is intended to provide general information on TERRACO's products and their methods of use. The prospective user is recommended to determine the suitability of TERRACO's suggestions and products before adopting them on a commercial scale.

For technical enquiries please contact your nearest Terraco representative:

ALGERIA:

SARL Terraco Algeria
Tel: +213 (0)23 23 07 80
Fax: +213 (0)23 23 07 80
E-mail: terraco@terraco.dz
Web: www.terraco.dz

CHINA:

Terraco Architectural Coatings China Co., Ltd.
Tel: +86 (0)20 8759 4742
Fax: +86 (0)20 8526 8056
E-mail: sales@terraco.com.cn
Web: www.terraco.com.cn

Terraco Chemical (Shanghai) Co., Ltd.

Tel: +86 (0)21 621020 48 / 18
Fax: +86 (0)21 625205 47
Email: sales@terraco.com.cn
Web: www.terraco.com.cn

EGYPT:

Terraco Egypt Chemical Industries S.A.E.
Tel: +20 (0)22 29184 53 / 57 / 58
Fax: +20 (0)22 29184 80
E-mail: terraco@terraco.com.eg
Web: www.terraco.com.eg

JORDAN:

Jordan Swedish Polymers Industrial Corp.
Tel: +962 (0)6 553 8751
Fax: +962 (0)6 553 6560
E-mail: terraco@nol.com.jo
Web: www.terraco.jo

IRELAND:

Terraco Technical Centre, Ireland
Tel: +353 (0) 1 2819 045
E-mail: technical-centre@terraco.com
Web: www.terraco.com

RUSSIA:

OOO Terraco Industry, Kirjach
Tel: +7 (0)495 9212 237
Fax: +7 (0)495 6273 881
E-mail: adm@terraco.ru
Web: www.terraco.ru

OOO Terraco Vostok Ltd

Tel: +7 (0)4212 410563
Fax: +7 (0)4212 410591
E-mail: terracovostok@terrakovostok.ru
Web: www.terraco.com

SOUTH KOREA:

Terraco Korea Co., Ltd
Tel: +82 (0) 2 5611 551
Fax: +82 (0)2 5671 771
E-mail: terraco@terraco.co.kr
Web: www.terraco.co.kr

THAILAND:

Terraco Industry (Thailand) Limited
Tel: +66 (0)2 946 68 56 / 58
Fax: +66 (0)2 946 68 59
E-mail: terraco@terraco.co.th
Web: www.terraco.com

TURKEY:

Terraco Yapi Malzemeleri Sanayi Ve Ticaret AS
Tel: +90 (0)222 236 0423
Fax: +90 (0)222 236 0425
E-mail: terraco@terraco.com.tr
Web: www.terraco.com.tr

UAE:

Terraco UAE Ltd
Tel: +971 (0) 4 326 2699
Fax: +971 (0) 4 326 2733
E-mail: terraco@terraco.ae
Web: www.terraco.com

UK:

ADDAGRIP
Tel: +44 (0)1825 761 333
E-mail: sales@addagrip.co.uk
Web: www.addagrip.co.uk / www.terraco.com

VIETNAM:

Terraco Vietnam Co., Ltd
Tel: +84 (0)650 3 820 100
Fax: +84 (0)650 3 820101
E-mail: terraco@terraco.com.vn
Web: www.terraco.com