








5 SIDE PROTECTION SEALER FOR MARBLES AND NATURAL STONES AGAINST STAINING AND DAMPNESS FROM SUBSTRATE.

MarbleCare SR is a water based emulsion of silane siloxane polymers that stops contaminants rising up from the substrate to the material surface (salts, tannin, oxides etc.) and prevents the formation of streaks and/or stains on the externals stone surface. To be applied before laying to prevent rising damp. To be applied on all four sides and bottom side prior to fixing on prepared surface floor.



APPLICATION:

- · Mixing: Mix for 5 minutes before using.
- Apply 1 coat of Marblecare SR on the entire surface using brush or roller. Allow the material to saturate the surface for 3 -5
 minutes. Remove any non-absorbed materials from the tile with a clean towel or absorbent paper.

Note: Highly porous substrates may require application of a second coat. After 2 - 4 hours of application, test the surface by applying water droplets. In case of absorption, apply a second coat.

Allow the material to dry for 12 hours prior to fixing of stones. Consult Terraco Technical Team for compatible adhesive.

AREAS OF USE:

Excellent sealer for most natural stones such as:

- Marble
- Limestone
- Sandstone
- Granite
- Slate
- Terravertine

TOOLS:



Brush



ADVANTAGES:

- Protects the substrate against water absorption and most stains.
- · Economical and easy to use
- Does not affect the adhesion of stone on substrate.
- Can be used for interior and exterior application
- Reduces freeze/thaw damage
- · Leaves a tack free natural surface
- Reduces efflorescence

TECHNICAL INFORMATION:

Specific Gravity

Colour Milky white liquid

Application Temperature 50°C to 40°C

Material Consumption
 150 - 200 gm/m²/coat depending on substrate conditions

• Storage 12 months in original unopened

container

Packaging 5kg and 20kg plastic pails







www.terraco.com

SWEDEN · UK · IRELAND · RUSSIA · TURKEY · ALGERIA · EGYPT · JORDAN · UAE · THAILAND · VIETNAM · CHINA · KOREA