IIII TERRACO®





Handycoat[®] Interior

Suitable for Most Building Surfaces.

Handycoat Interior is a ready-mixed filler used for skimming and gypsum board jointing. It is made from a selected blend of acrylic polymers and precisely graded fillers to ensure excellent product performance.

Using Handycoat Interior makes it easier to prepare gypsum boards, sand-cement renders and cement board surfaces for painting. It gives a uniform finish when repairing and touching up old or new surfaces.



WHY CHOOSE HANDYCOAT INTERIOR?

EASY TO APPLY

Developed to help applicators repair and touch up surfaces in an easy and efficient way.

NO PRIMING REQUIRED

Designed to be painted on, without the use of a primer.

LOWER PAINT CONSUMPTION

Reduces consumption of paint during overcoating.



OTHER FEATURES AND BENEFITS

- Paintable within 24 hours
- Good vapour permeability allowing susbstrate to breathe
- Outstanding flexibility avoiding shrinkage, cracking and flaking

AREAS OF USE

- Gypsum
- Gypsum boards
- Cementitious materials
- Sprayplasters
- Wood
- Sand-cement renders
- Cement boards
- Most interior surfaces

HANDYCOAT INTERIOR IS PERFECT FOR

- Skimming walls and ceilings
- Conventional taping and jointing systems
- Repairing damages, cracks or nail holes
- Areas around door and window architraves







HOW TO USE

- 1 Apply the filler in a thin even layer
- 2 If a thick coat is necessary, apply several thin layers, allowing to dry between layers.
- 3 Lightly sand the final surface before painting, within 24 hour of application.

 ${}^\star \text{For detailed}$ usage instructions, please refer to the Technical Data Sheet

TECHNICAL DATA

Dilution	With water if required
Coverage	1.6-1.7 kg/m2/mm
Specific Gravity	1.75
Colour	Off-white
Standard Compliance	ASTM C-475
Packaging	5 and 25 kg plastic pails
Storage	18 months in original unopened containers.







www.terraco.com

SWEDEN • UK • IRELAND • RUSSIA • TURKEY • ALGERIA • EGYPT JORDAN • UAE • THAILAND • VIETNAM • CHINA • KOREA