

The logo for Terraco, featuring four slanted vertical bars of increasing height to the left of the word "TERRACO" in a bold, white, sans-serif font. A registered trademark symbol (®) is located at the top right of the word. The logo is set against a solid blue background.

//// TERRACO®

The product name "Terralite FlexStone" is displayed in white text on a purple, rounded rectangular background. "Terralite" is in a larger font size than "FlexStone". A small trademark symbol (™) is positioned to the right of "Terralite".

Terralite™
FlexStone



Multi Coloured Stone Effect Coating

Terralite is a range of decorative coatings created with naturally graded stone aggregates encapsulated in a clear resin binder that gives a natural stone effect.

Terralite FlexStone is a trowel applied multi-colour decorative finish specifically designed for windy areas on large elevations where spray application is not ideal.



Excellent weather and UV resistance

Terralite FlexStone has been developed to withstand extreme climatic conditions like the extreme heat of Middle Eastern deserts, severe monsoons of Asia and the harsh cold of the Scandinavian region.



Excellent abrasion resistance

Terralite FlexStone is designed to withstand impact and abrasion in low lying areas of buildings which are exposed to everyday wear and tear.



UV Stable

Terralite FlexStone has been manufactured using UV stabilizers to protect the coating from the damaging UV rays. These UV stabilizers absorb or screen out UV radiation, preventing surface damage.



Other Features and Benefits

- ◆ Water resistant
- ◆ Washable
- ◆ Algae and fungi resistant
- ◆ Long shelf life
- ◆ Available in bespoke range of colours



Terralite FlexStone is perfect for

- ◆ Exterior and Interior Facades
- ◆ New work and renovation / retrofit projects
- ◆ Industrial and commercial complexes
- ◆ Housing complexes

Areas of use

- ◆ Concrete
- ◆ Cement Render
- ◆ Wood

Recommended for:



How to use

New work*

- 1 Prime surfaces with 1 coat of Penetrating Primer Plus Pigmented.
- 2 Apply Terralite FlexStone using a steel trowel and allow to set for 2 minutes and finish with a wet trowel to get smooth and even finish.

Renovation / Retrofit*

- 1 All cracks, chips, voids and damages should be repaired with appropriate filler.
- 2 Prepare surface by removing loose or flaking paint, grease, dirt and grime.
- 3 Prime surfaces with a coat of Penetrating Primer Plus Pigmented.
- 4 Proceed as per new work.

*Contact your local Terraco representative for site specific method statement



Guideline Spread Rates

Onto cementitious substrate.

P Primer Pigmented	0.15-0.2 kg/m ²
Terralite FlexStone	1.2-1.5 kg/m ²

*Material consumption may vary depending on substrate conditions



Technical Data

Coating Thickness	0.8-1.0 mm
Specific Gravity	1.28
Packaging	20kg plastic pails
Storage	12 months in original unopened containers



www.terraco.com

SWEDEN • UK • IRELAND • RUSSIA • TURKEY • ALGERIA • EGYPT
SOUTH AFRICA • JORDAN • UAE • THAILAND • VIETNAM • CHINA • KOREA

